# **EROSION CONTROL**

#### POND CONSTRUCTION AND MAJOR REPAIR

Construction or major repair of a permanent water pond for the purpose of preventing, stopping, or controlling erosion as part of approved NRCS erosion control structure. The project must provide habitat diversity wildlife benefits. and Creation/restoration of shallow primary water areas as wetlands production and associated water level control and management should be associated with ponds at every opportunity. A minimum of one project must be implemented



and maintained every 10 years to qualify.

#### **GULLY SHAPING**

Reducing erosion rates on severely eroded areas by smoothing with top soil to acceptable grades and reestablishing vegetation, primarily native vegetation, with sensitivity to existing wildlife cover and woody vegetation that provides travel corridors. Area must be interseeded with species that provide food and/or cover for wildlife to be applicable (see range enhancement guidelines). This practice may include the feeding of large numbers of cattle on gully sites to contour the eroded areas by way of hoof action to aid in the recovery of the site. A minimum of one project must be implemented and maintained every 10 years to qualify.

### STREAMSIDE, POND, AND WETLAND REVEGETATION

Re-vegetating areas along creeks, streams, ponds, and wetlands to reduce erosion and sedimentation, stabilize stream banks, improve plant diversity, and improve wildlife value of sensitive areas. This practice can include: (a) the construction of permanent or temporary fences to exclude, limit, or seasonally graze livestock in order to prevent erosion; (b) the use of native hay to slow and spread water runoff in areas where vegetation has been recently reestablished (seeds in the hay aid in re-vegetation); (c) establishing vegetative buffer areas or filter strips along water courses or other runoff areas; (d) establishment of 3:1 upland buffer to lake basin/wetland acreage in diverse grass/legume/forb mixture to prevent sedimentation; (e) the installation of rip-rap,

dredge spoil, or other barrier material - placement of material along erodible embankments to prevent erosion and protect wildlife habitat; (f) the establishment of stream crossings to provide permanent low water crossings in order to reduce or prevent erosion. A minimum of one project must be implemented and maintained every 10 years.

Proposed streamside, pond, and wetland restoration project(s) may include the following techniques:

- o native hay bales
- o fencing
- o filter strips
- o seeding upland buffer
- o rip-rap, etc.
- stream crossings

## PLANT ESTABLISHMENT ON CRITICAL AREAS (erodible)

Primarily for erosion control, the establishment of native woody or herbaceous vegetation can also provide food and/or cover for wildlife and restore native habitat. This practice can include: (a) establish and manage wind breaks/shelter-belts by planting multi-row shelter-belts (at least 4 rows in 120' width by 1/4 mile in length), renovate old shelter-belts (re-fence, root-prune, and replace dead trees), and establish shrub mottes, improve plant diversity, and improve wildlife habitat; (b) establish perennial vegetation on terraces and field borders (30 yard minimum width) to reduce erosion, improve plant diversity, and improve wildlife habitat; (c) conservation tillage/notill farming practices by leaving waste grain and stubble on the soil surface until the next planting season to provide supplemental food or cover for wildlife, control erosion, and improve the soil tilth; (d) manage Conservation Reserve Program cover by maintaining perennial cover established under the Conservation Reservation Program (expired contracts) on erodible sites using proper management techniques such as having, prescribed grazing or prescribed burning. A minimum of 10 seedlings per acre must be planted and maintained annually on 10 acres or a minimum of 10% (whichever is smaller) of the total designated area treated annually.

#### DIKE/LEVEE CONSTRUCTION/MANAGEMENT

To establish/maintain wetlands or slow runoff to control or prevent erosion, and to provide habitat for wetland dependent wildlife. Levee management may include reshaping or repairing damage caused by erosion, re-vegetating levee areas to reduce erosion and sedimentation, and stabilizing levees. This practice may include fencing to control and manage grazing use or installation of water control structures. A minimum of one project must be completed and maintained every 10 years.

# **ESTABLISH WATER DIVERSION**

Install water diversion systems that will protect erodible soils and divert water into wetlands to provide habitat for resident and migratory water birds and wetland dependent species. Seed diversion areas to species tolerant of seasonally standing water. A minimum of one project must be completed and maintained every 10 years.



A flashboard riser box attaches to a pipe installed in a levee to create a shallow water wetland for wildlife.